

(12) United States Patent

Navarrini

4,550,132 A 10/1985 Capriotti 4,564,662 A 1/1986 Albin 4,619,983 A 10/1986 Yamabe et al.

(10) Patent No.: US 7,160,967 B2

(45) **Date of Patent:**

Jan. 9, 2007

	1 144 741 1 1	111	(43)	Date of	ı atem	Juli. 9, 2007
(54)		VINYL ETHERS AND POLYMERS		4,394 A		Yamabe et al.
	OBTAIN	ABLE THEREFROM		3,395 A		Caywood, Jr.
(75)		***		0,328 A		Kawachi et al.
(75)	Inventor:	Walter Navarrini, Milan (IT)		4,045 A	9/1987	
(72)	A:	Colour Colour Con A Miles (IT)		4,465 A		Moggi et al.
(73)	Assignee:	Solvey Solexis S.p.A., Milan (IT)		3,300 A		Brinduse et al.
(*)	Notice:	Subject to any disalaimor the term of this		5,165 A		Arcella et al.
(')	Notice.	Subject to any disclaimer, the term of this		2,891 A		Albin et al.
		patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.		6,190 A		Morita et al.
		0.5.C. 154(b) by 0 days.		9,717 A		Giannetti et al.
(21)	Annl No	: 11/115,173		0,588 A		Brinduse et al.
(21)	прри 140.	. 11/113,173	,	4,006 A		Giannetti et al.
(22)	Filed:	Apr. 27, 2005		2,390 A		Grootaert et al.
()	1 110 41.	1.p. 2., 2000		6,770 A		Marchionni et al.
(65)		Prior Publication Data		2,171 A		Grootaert et al.
				3,622 A		Naraki et al.
	US 2005/0	0192420 A1 Sep. 1, 2005		8,852 A	8/1990	
	ъ.			7,975 A		Carlson et al.
	Re	lated U.S. Application Data		0,283 A		Visca et al.
(62)	Division o	of application No. 09/840,527, filed on Apr.		6,123 A		Guenthner et al.
` ′		now Pat. No. 6,963,013.		4,092 A		Marraccini et al.
				9,842 A		Sianesi et al.
(30)	F	oreign Application Priority Data	5,17	3,553 A		Albano et al.
	21 2000	(IT) MI2000 4 0001		2,342 A		Feiring et al.
Ap	r. 21, 2000	(IT) MI2000A0901	5,21	4,106 A		Carlson et al.
51)	Int. Cl.		5,23	5,074 A	8/1993	Navarrini et al.
(51)	C08F 16/	24 (2006.01)	5,26	0,392 A	11/1993	Arcella et al.
(50)		,	5,26	0,393 A	11/1993	Arcella et al.
(52)	U.S. Cl		5,26	2,490 A	11/1993	Kolb et al.
/=a\		568/669; 568/615; 568/674; 568/677	5,26	8,405 A	12/1993	Ojakaar et al.
(58)	Field of C	Classification Search				
	See applic	eation file for complete search history.			(Con	tinued)
(56)		References Cited		FOREI	GN PATE	NT DOCUMENTS
	U.	S. PATENT DOCUMENTS	BE	8	40099	9/1976
	2,520,338 A	8/1950 Robertson				
	2,525,628 A				40	
	3,085,083 A	4/1963 Schreyer			(Con	tinued)
	3,132,123 A			O'	THER PU	BLICATIONS
	3,291,843 A			Ü		
	3,450,684 A	-	Copy of E	European S	earch Repor	rt for EP 01 10 8598.
	3,451,908 A 3,635,926 A	6/1969 Sianesi et al. 1/1972 Gresham et al.			(Com	time al)
	3,752,787 A				(Con	tinued)
	3,810,874 A		Primary	Examiner	-David V	V. Wu
	3,817,960 A				r—Henry	
	3,876,654 A					<i>n</i> —Kenyon & Kenyon LLP
	3,896,179 A	7/1975 Resnick	(, ,,		,	
	4,035,565 A	1	(57)		ABST	CRACT
	4,181,679 A		. ,			
	4,214,060 A	-				
	4,233,427 A	2				e formula CFX=CXOCF ₂ OR
	4,243,770 A		wherein	K is a C	$_2$ – C_6 lines	ar, branched or C ₅ -C ₆ cyclic
	4,259,463 A					C ₂ -C ₆ linear, branched (per
	4,287,320 A					ning from one to three oxyger
	4,340,750 A					yl or fluorooxyalkyl group a
	4,368,308 A					n from 1 to 2 atoms, equal o
	4,418,186 A 4,487,903 A					ollowing: H, Cl, Br, I; X=F, H
	4,487,903 A 4,515,989 A					mers obtainable polymerizing
	4,515,989 A 4,529,784 A			-	thers with	at least another polymerizable
	4,550,132 A		monome	r.		

15 Claims, No Drawings

U.S. PATI	NT DOCUMENTS	EP 0 683 181 9/1997
5,285,002 A 2/1	94 Grootaert	EP 0690880 9/1997
	94 Navarrini et al.	EP 0 976 706 2/2000
	194 Navamm et al. 194 Oka et al.	EP 0835270 8/2000
	94 Hung et al.	EP 01 10 8596 11/2003
	95 Grootaert	FR 2305462 A 10/1976
	95 Oka et al 526/247	GB 1 514 700 6/1978
2,101,010 11 2/1	95 Dower	GB 1528341 10/1978
	96 Varney et al.	GB 1528342 10/1978
	96 Arcella et al.	IR 42664 9/1980
	97 Coggio et al.	IR 42665 9/1980 NL 7603217 9/1976
	97 Farnham et al.	NL 7603217 9/1976 NL 7810787 3/1979
	97 Chiodini et al.	WO WO94/21697 9/1994
	97 Chiodini et al.	WO 9702300 A 1/1997
	97 Kruger et al 526/247	WO WO98/46657 10/1998
	98 Chiodini et al.	WO WO98/46658 10/1998
	99 Saito et al.	WO 99 48939 A 9/1999
	99 Saito et al.	
	99 Saito et al 526/247	
	01 Worm et al.	WO WO00/12574 9/2000 WO WO01/27194 4/2001
	01 Worm et al.	WO WO01/27194 4/2001 WO WO 01 46107 6/2001
	04 Grootaert et al 526/247	WO WO-02/060968 A1 * 8/2002
	01 Navarrini	WO WO-02/000908 AT 7 8/2002
		OTHER RUDI ICATIONS
FOREIGN PA	TENT DOCUMENTS	OTHER PUBLICATIONS
CA 1076298	4/1980	Copy of International Search Report for PCT/US99/03490.
		*Maskornik, M. et al. "ECD-006 Fluoroelastomer—A high perfor-
CA 1094247 DE 1 971 806	1/1981	mance engineering material". Soc. Plast Eng. Tech. Pao. (1974), 20,
DE 19/1 800 DE 2612360	11/1967	675-7.
DE 2012300		0/3-/.
DE 107 13 806	9/1976 10/1997	
DE 197 13 806 EP 0 120 462	10/1997	* "Development of Vulcanizable Elastomers Suitable For Use In
EP 0 120 462	10/1997 10/1984	
EP 0 120 462 EP 0120462	10/1997 10/1984 10/1984	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967.
EP 0 120 462 EP 0120462 EP 0 130 052	10/1997 10/1984 10/1984 1/1985	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4),
EP 0 120 462 EP 0120462 EP 0 130 052 EP 0136596	10/1997 10/1984 10/1984 1/1985 1/1985	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6.
EP 0 120 462 EP 0120462 EP 0 130 052 EP 0136596 EP 0 136 596	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985	 * "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins,"
EP 0 120 462 EP 0120462 EP 0 130 052 EP 0136596 EP 0 136 596 EP 0 178 935	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985 4/1986	 * "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361,
EP 0 120 462 EP 0120462 EP 0 130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299	10/1997 10/1984 10/1984 1/1985 1/1985 4/1986 5/1986	 * "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR).
EP 0 120 462 EP 0120462 EP 0 130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299	10/1997 10/1984 10/1984 1/1985 1/1985 4/1986 5/1986 5/1986	 * "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-
EP 0 120 462 EP 0120462 EP 0 130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0 189 138	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985 4/1986 5/1986 5/1986 10/1986	 * "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical
EP 0 120 462 EP 0120462 EP 0 130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299 EP 0 199 138 EP 0199138	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985 4/1986 5/1986 5/1986 10/1986	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated
EP 0 120 462 EP 0120462 EP 0 130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299 EP 0 199 138 EP 0199138 EP 0 335 705	10/1997 10/1984 10/1984 1/1985 1/1985 4/1986 5/1986 5/1986 10/1986 10/1986	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No.
EP 0 120 462 EP 0120462 EP 0 130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299 EP 0199 138 EP 0199 138 EP 0 335 705 EP 0 338 755	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985 4/1986 5/1986 5/1986 10/1986 10/1986 10/1989	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No. 10, pp. 2268-2272, Oct. 1978.
EP 0 120 462 EP 0120462 EP 0130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299 EP 0199 138 EP 0199 138 EP 0199 138 EP 0 335 705 EP 0 338 755 EP 0 335755	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985 4/1986 5/1986 5/1986 10/1986 10/1986 10/1989 10/1989	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No. 10, pp. 2268-2272, Oct. 1978. G. Marchionni et al., "Photochemical Fluorination of
EP 0 120 462 EP 0120462 EP 0130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299 EP 0199 138 EP 0199 138 EP 0199 138 EP 0335 705 EP 0 338 755 EP 0335755 EP 0 410 351	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985 4/1986 5/1986 5/1986 10/1986 10/1986 10/1989 10/1989 1/1991	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No. 10, pp. 2268-2272, Oct. 1978. G. Marchionni et al., "Photochemical Fluorination of Perfluoropolyether Functional Derivatives," J. Fluorine Chemistry,
EP 0 120 462 EP 0120462 EP 0130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299 EP 0199 138 EP 0199 138 EP 0199 138 EP 0 335 705 EP 0 338 755 EP 0 335755	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985 4/1986 5/1986 5/1986 10/1986 10/1986 10/1989 10/1989	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No. 10, pp. 2268-2272, Oct. 1978. G. Marchionni et al., "Photochemical Fluorination of Perfluoropolyether Functional Derivatives," J. Fluorine Chemistry, 47: 515-525, 1990.
EP 0 120 462 EP 0120462 EP 0130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299 EP 0199 138 EP 0199138 EP 0335 705 EP 0 338 755 EP 0 035755 EP 0 410 351 EP 0410351 EP 0410351 EP 290848	10/1997 10/1984 10/1984 1/1985 1/1985 4/1986 5/1986 5/1986 10/1986 10/1986 10/1989 10/1989 10/1989 1/1991 1/1991	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No. 10, pp. 2268-2272, Oct. 1978. G. Marchionni et al., "Photochemical Fluorination of Perfluoropolyether Functional Derivatives," J. Fluorine Chemistry, 47: 515-525, 1990. Worm Opposition 1, dated Jul. 30, 2004.
EP 0 120 462 EP 0120462 EP 0130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299 EP 0199 138 EP 0199138 EP 0335 705 EP 0 338 755 EP 0 035755 EP 0 410 351 EP 0410351 EP 0410351 EP 290848	10/1997 10/1984 10/1984 1/1985 1/1985 4/1986 5/1986 5/1986 10/1986 10/1986 10/1989 10/1989 10/1989 1/1991 1/1991 1/1991 7/1991	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No. 10, pp. 2268-2272, Oct. 1978. G. Marchionni et al., "Photochemical Fluorination of Perfluoropolyether Functional Derivatives," J. Fluorine Chemistry, 47: 515-525, 1990. Worm Opposition 1, dated Jul. 30, 2004. Worm Preliminary Motion, dated Jul. 30, 2004.
EP 0 120 462 EP 0120462 EP 0130 052 EP 0136596 EP 0 136 596 EP 0 178 935 EP 0 182 299 EP 0182299 EP 0199 138 EP 0199 138 EP 0335 705 EP 0 338 755 EP 0 335 755 EP 0 410 351 EP 0410 351 EP 0410 351 EP 290848 EP 290848	10/1997 10/1984 10/1984 1/1985 1/1985 4/1986 5/1986 5/1986 10/1986 10/1986 10/1989 10/1989 10/1989 1/1991 1/1991 1/1991 7/1991	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No. 10, pp. 2268-2272, Oct. 1978. G. Marchionni et al., "Photochemical Fluorination of Perfluoropolyether Functional Derivatives," J. Fluorine Chemistry, 47: 515-525, 1990. Worm Opposition 1, dated Jul. 30, 2004. Navarrini Opposition 1, dated Aug. 1, 2004.
EP 0 120 462 EP 0120462 EP 0130 052 EP 0136596 EP 0136 596 EP 0 178 935 EP 0182 299 EP 0182 299 EP 0199 138 EP 0199 138 EP 0335 705 EP 0 338 755 EP 0 410 351 EP 0410 351 EP 0410 351 EP 290848 EP 290848 EP 06332 57	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985 4/1986 5/1986 5/1986 10/1986 10/1989 10/1989 10/1989 1/1991 1/1991 1/1991 7/1991 31 * 7/1991 31 1/1995 11/1995	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No. 10, pp. 2268-2272, Oct. 1978. G. Marchionni et al., "Photochemical Fluorination of Perfluoropolyether Functional Derivatives," J. Fluorine Chemistry, 47: 515-525, 1990. Worm Opposition 1, dated Jul. 30, 2004. Navarrini Opposition 1, dated Aug. 1, 2004. Navarrini Preliminary Motion 1, dated Apr. 23, 2004.
EP 0 120 462 EP 0120462 EP 0130 052 EP 0136596 EP 0136 596 EP 0 178 935 EP 0182 299 EP 0182 299 EP 0199 138 EP 0199 138 EP 0335 705 EP 0 338 755 EP 0 410 351 EP 0410 351 EP 290848 EP 290848 EP 0633257 EP 0 683 181	10/1997 10/1984 10/1984 1/1985 1/1985 4/1985 4/1986 5/1986 10/1986 10/1986 10/1989 10/1989 10/1989 1/1991 1/1991 1/1991 7/1991 31 * 7/1991 31 1/1995 11/1995 11/1995	* "Development of Vulcanizable Elastomers Suitable For Use In Contact With Liquid Oxygen" J. Macromol. SciPhys., B1 (4), 815-830, Dec. 1967. * Knunyants, I. L. et al., Izv. Akad. Nauk. SSR, Ser. Khim 1964 (2), 384-6. I. L. Knunyants et al. "Fluorinated Diiodalkanes and Diolefins," Bulletin of the Academy of Sciences, USSR, Feb. 1964, 359-361, vol. 2 (Academy of Sciences of the USSR). S.V. Kartsov et al., "The role of the reactor surface in the liquid-phase oxidation of hexafluoropropylene," Institute of Chemical Physics, Academy of Sciences of the USSR, Moscow (Translated from Izvestiya Akademii Nauk SSSR, Seriya Khimicheskaya, No. 10, pp. 2268-2272, Oct. 1978. G. Marchionni et al., "Photochemical Fluorination of Perfluoropolyether Functional Derivatives," J. Fluorine Chemistry, 47: 515-525, 1990. Worm Opposition 1, dated Jul. 30, 2004. Navarrini Opposition 1, dated Aug. 1, 2004.

FLUOROVINYL ETHERS AND POLYMERS OBTAINABLE THEREFROM

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a divisional application of U.S. patent application Ser. No. 09/840,527, filed on Apr. 23, 2001, now U.S. Pat. No. 6,963,013, which is incorporated by reference herein.

The present invention relates to Fluorovinyl ethers, the process for preparing them and the polymers obtainable therefrom.

It is well known that perfluoroalkyl vinyl ethers are generally used as monomers for the olefin copolymerization, specifically copolymerization with tetrafluoroethylene, vinylidene fluoride, chlorotrifluoroethylene (CTFE), and/or hexafluoropropene. The introduction of small-amounts of perfluoroalkyl vinyl ethers in plastomeric polymers implies a higher polymer processability and better hot mechanical 20 properties. The introduction of high amounts of perfluorovinyl ethers in crosslinkable fluoropolymers implies elastomeric properties at low temperature of fluorinated rubbers.

The need was felt, in the fluorinated polymeric material field, to produce both plastomers having good properties at ²⁵ high temperatures, and elastomers having improved properties at low temperatures by using only one fluorovinyl ether.

Such properties at low temperatures can generally be expressed by the glass transition temperature Tg.

Furthermore the need was felt to have available amorphous or crystalline copolymers having a low content of C(O)F end groups. A lower content of C(O)F end groups leads to obtain polymers having a higher thermal stability. A lower Tg allows to have elastomeric polymers which can be used at lower temperatures and therefore to have available elastomers with a wider use range. To obtain the combination of the above mentioned properties, fluorovinyl ethers must have a high unitary capability to modify the base backbone properties, as well as high reactivity to be used as comonomers both in plastomeric and in elastomeric fluoropolymers. It was desirable to have available vinyl ethers obtainable by simple processes having a limited number of steps. Preferably it would be desirable to have available a continuous process for preparing said vinyl ethers.

To solve the above identified technical problem, fluorovinyl ethers having different structural properties, have been proposed in the prior art. However from the prior art, hereinafter described, various unsolved problems result evident in the perfluorovinyl ether synthesis and in the preparation of the corresponding polymers having the combination of the above mentioned properties.

U.S. Pat. No. 3,132,123 describes the preparation of perfluoroalkyl vinyl ethers, of the corresponding homopolymers and copolymers with TFE. Homopolymers are obtained under extreme experimental conditions, by using polymerization pressures from 4,000 to 18,000 atm. The perfluoromethylvinylether (PMVE) homopolymer is an elastomer: the Tg is not reported.

The general formula of the described vinyl ethers is the following:

$$CF_2 = CFOR^{O}_{F}$$

wherein R_F^O is a perfluoroalkyl radical preferably from 1 to 65 5 carbon atoms. A process for preparing these vinyl ethers is described in U.S. Pat. No. 3,291,843 wherein the starting

2

acylfluoride is solidified and pyrolized with carbonates also in the presence of solvents. By this process undesired hydrogenated by products are obtained.

U.S. Pat. No. 3,450,684 relates to vinyl ethers having the formula:

wherein X⁰=F, Cl, CF₃, H and n' can range from 1 to 20. Also homopolymers obtained by UV polymerization are reported. The exemplified copolymers are not characterized by their properties at low temperatures.

U.S. Pat. No. 3,635,926 relates to the emulsion copolymerization of perfluorovinyl ethers with TFE, showing that the presence of —C(O)F acylfluoride end groups makes the polymers unstable. The same phenomenon was already reported in U.S. Pat. No. 3,085,083 in the perfluorovinyl ether polymerization systems in solvent.

U.S. Pat. No. 3,817,960 relates to the preparation and polymerization of perfluorovinyl ethers having the formula

wherein n" can range from 1 to 5. The compound synthesis is complex, it requires three steps. The preparation of the starting compound $CF_3O(CF_2O)_{n''}CF_2C(O)F$ is carried out by oxidation at low temperature in the presence of U.V. radiations; besides the condensation with HFPO (hexafluoropropenoxide) and the subsequent alkaline pyrolysis is necessary. No data on the above indicated properties are reported. With regard to this see Patent application U.S. Pat. No. 5,910,552.

U.S. Pat. No. 3,896,179 relates to the separation of "primary" isomers of perfluorovinyl ethers, for example of $CF_3CF_2CF_2OCF = CF_2$ from the corresponding less stable "secondary" isomers $CF_3(CF_3)CFOCF = CF_2$. The latter are undesired products as regards both the polymer preparation and the poor properties of the obtained polymers.

U.S. Pat. No. 4,340,750 relates to the preparation of perfluorovinyl ethers having the formula

$$CF_2 = CFOCF_2R^{\circ}X^1$$

wherein R_f^o is a C_1 – C_{20} perfluoroalkyl optionally containing oxygen, X^1 —H, Cl, Br, F, COOR o , CONR o R 1 wherein R^o is a C_1 – C_{10} alkyl group and R^1 represents H or a C_1 – C_{10} alkyl group. In the preparation of these compounds an acylfluoride together with iodine and tetrafluoroethylene is used, avoiding the final step of the acylfluoride pyrolysis which comes from the perfluoro-propene epoxide, by a deiodofluorination reaction, which takes place with low yields.

U.S. Pat. No. 4,487,903 relates to the preparation of fluoroelastomeric copolymers (i.e., elastomeric fluoropolymers) using perfluorovinyl ethers having the formula:

$$CF_2 = CF(OCF_2CFY^O)_n \circ OX^2$$

wherein n^0 ranges from 1 to 4; $Y^O = F$, Cl, CF_3 , H; X^2 can be $C_1 - C_3$ perfluoroalkyl group, $C_1 - C_3$ ω -hydroperfluoroalkyl group, $C_1 - C_3$ ω -chloroperfluoroalkyl group. The polymer has a content of fluorovinyl ether units ranging from 15 to 50% by moles. These vinyl ethers give copolymers which at low temperatures have better properties than those of the above mentioned perfluorovinyl ethers PVE (perfluoropropyl vinyl ether) and MVE type. In the patent it is disclosed that in order to have good properties at low temperature, the presence of at least two ether bonds in the side chain adjacent to the double bond is required. Furthermore from

the patent it results that for values higher than 4 it is difficult to purify the monomers and the effect on the decrease of the polymer T_g is lower. Besides the reactivity of the described vinyl ethers is very low and it is difficult to obtain polymers having a high molecular weight able to give good elastomeric properties. A TFE/perfluorovinyl ether copolymer (n^o =2) 73/27% by moles with Tg of –32° C. is exemplified. However the polymer is obtained with very long reaction times (96 hours of polymerization).

Patent EP 130,052 describes the perfluoro(vinyl polyether) (PVPE) polymerization which leads to amorphous perfluoropolymers with a T_g ranging from -15 to -100° C. The described polymers have T_g values reaching up to -76° C.; the further T_g decrease is obtained by using perfluoropolyethers as plasticizers. In the patent copolymers and 15 terpolymers of TFE and MVE with vinylethers (PVPE) having the formula

$$CF_2 = CFO(CF_2CF(CF_3)0)_{n'''}R^o_{f^2}$$

are described, wherein n''' ranges from 3 to 30 and R^o_f is a perfluoroalkyl group. Due to purification difficulties, the used vinyl ethers are vinylether mixtures with different n''' values. According to said patent the most evident effect on the T_g decrease is shown when n' is equal to or higher than 3, preferably higher than 4. According to the polymerization examples described in said patent the final mass of the polymer, besides the hot and under vacuum treatment, must then be washed with Freon® TF (chlorofluorocarbon) in order to remove all the unreacted monomer (PVPE). From the Examples it results that the reactivity of all the described monomers (PVPE) is poor.

U.S. Pat. No. 4,515,989 relates to the preparation of new intermediates for the fluorovinyl ether synthesis. According to the patent the vinylether synthesis is improved by using an intermediate able to more easily decarboxylate. For its preparation fluoroepoxides of formula:

wherein

X³=Cl, Br

are used.

U.S. Pat. No. 4,619,983 describes the copolymerization of VDF with vinyl ethers having the formula: 50

wherein X^4 is a C_3 – C_9 oxyperfluoroalkyl radical containing from 1 to 3 oxygen atoms. The obtained polymers are not perfluorinated polymers and show a poor stability to alcohols.

U.S. Pat. No. 4,766,190 relates to the polymerization of perfluorovinylpolyethers (PVPE) similar to those of U.S. Pat. No. 4,487,903 with TFE and low perfluoropropene percentages, in order to improve the mechanical properties of the obtained polymers.

Patent EP 338,755 relates to the preparation of perfluorinated copolymers by using direct fluorination of partially fluorinated copolymers. More reactive partially fluorinated monomers are used, subjecting the obtained polymers are fluorinated with elemental fluorine. The fluorination step

4

requires a supplementary process unit, besides in this step elemental fluorine is used, which is a highly oxidizing gas, with the consequent precautions connected to its use. Besides in the patent it is stated that in order not to compromise the fluorination reaction and the properties of the obtained polymer, using the invention process the percentage of the comonomer in the polymer cannot exceed 50% by moles.

U.S. Pat. No. 5,268,405 reports the preparation of perfluorinated rubbers having a low Tg, by the use of high viscosity perfluoropolyethers as plasticizers of perfluorinated rubbers (TFE/MVE copolymers). However during the use perfluoropolyether bleeds take place. This is true especially for the PFPE having a low molecular weight (low viscosity): in said patent, therefore, the high viscosity PFPE use is suggested, and therefore the low viscosity PFPEs must previously be removed from these last.

U.S. Pat. No. 5,350,497 relates to the preparation of perfluoroalkyl vinyl ethers by fluorination with elemental fluorine of hydrofluorochloroethers and subsequent dechlorination

U.S. Pat. No. 5,401,818 relates to the preparation of perfluorovinyl ethers of formula:

$$R^1/(OCF_2CF_2CF_2)_m$$
— OCF = CF_2

(wherein R_f^1 is a C_1 – C_3 perfluoroalkyl radical and m, is an integer ranging from 1 to 4) and of the corresponding copolymers having improved properties at low temperature. The preparation of said perfluorovinyl ethers is carried out by 7 steps, some of them have very low yields, and comprise also a fluorination with elemental F_2 . The reactivity of said perfluorovinyl ethers is anyhow low.

As it is shown from the above prior art, the perfluorovinyl ether synthesis generally involves a multistep process with low yields (U.S. Pat. Nos. 3,132,123 and 3,450,684), with additional purifications to remove undesired isomers (U.S. Pat. No. 3,896,179) and the need to control the undesired hydrogenated by-products (U.S. Pat. No. 3,291,843). Alternatively, in the synthesis substances acting as intermediates, which are suitably prepared, and which allow to eliminate said drawbacks (U.S. Pat. Nos. 4,340,750 and 4,515,989), are used.

Furthermore in some cases the vinylether preparation requires the fluorination with elemental fluorine of partially fluorinated intermediates (U.S. Pat. No. 5,350,497); or, to avoid synthesis and low reactivity problems of the perfluorovinyl ethers, fluorination of partially fluorinated polymers (EP 338,755) is suggested.

Other problems shown in the prior art relate to the low reactivity of the perfluorovinyl ethers, which makes it necessary the recovery of the unreacted monomers from the reaction raw products (English Patent UK 1,514,700), and the stability problems for the polymers having —C(O)F end groups (U.S. Pat. No. 3,635,926). These unstable end groups can be transformed by suitable reactants in order to increase the stability of the fluorinated polymer (EP 178,935).

Perfluoro(oxyalkyl vinyl ethers) are used to confer to the fluorinated rubbers good properties at low temperatures, and specifically to lower the copolymer glass transition temperature.

By increasing the perfluorooxyalkyl units forming the side perfluorooxyalkyl substituent, the $T_{\rm g}$ of the corresponding obtainable amorphous copolymers decreases, but at the same time the reactivity of the vinylether drastically decreases, making more evident the previously shown problems for the recovery of the unreacted monomer from the

raw polymerization products or from the polymer itself (U.S. Pat. No. 4,487,903-EP 130,052). In some cases, where the monomer cannot be completely removed by simple stripping under vacuum, more washings must then be carried out with fluorinated solvents to completely eliminate the 5 unreacted vinyl ethers from the polymeric mass.

The perfluoromethylvinylether (MVE) is used as comonomer in plastomeric fluoropolymers and, at higher concentrations, also in elastomeric fluoropolymers. In particular, in EP 633,257 and EP 633,274 MVE is polymerized with TFE in the presence of small amounts of PVE or dioxoles to obtain polymers with improved flex life.

The amorphous copolymers of TFE with perfluoromethylvinylether have a T_g around 0° C. or slightly lower (Maskornik, M. et al. "ECD-006 Fluoroelastomer—A High 15 Performance Engineering Material". Soc. Plast Eng. Tech. Pao. (1974), 20, 675–7).

The extrapolated T_g value of the MVE homopolymer is about -5° C. (J. Macromol. Sci.-Phys., B1(4), 815–830, December 1967).

In U.S. Pat. Nos. 5,296,617 and 5,235,074 there is described the reaction of hypofluorite, $CF_2(OF)_2$, with unsaturated products, which contemporaneously leads to the formation of the dioxolane derivative and to the fluorinated olefin. Patent EP 683,181 describes the reactivity of CF_2 (OF)₂ towards olefins, leading to the formation of linear reaction products between one hypofluorite molecule and two molecules of the same olefin, producing symmetric dienes

The Applicant has surprisingly and unexpectedly found ³⁰ that it is possible to solve the above mentioned technical problems by using special fluoro vinyl ethers that are furthermore easily synthesized by a continuous process.

An object of the present invention is fluorovinyl ethers of general formula:

$$CFX = CXOCF_2OR \tag{I}$$

wherein R is a C_2 – C_6 linear, branched or C_5 – C_6 cyclic (per)fluoroalkyl group, or a C_2 – C_6 linear or branched (per) fluoro oxyalkyl group containing from one to three oxygen atoms. When R is a fluoroalkyl or fluorooxyalkyl group as above defined, it can contain 1 or 2 atoms, the same as or different from each other, selected from the following: H, Cl, Br, I; X=F, H. The term (per)fluoro refers to a molecule in which from one up to all of the hydrogens capable of being replaced with fluorine are replaced with fluorine.

The fluorovinyl ethers of general formula:

$$CFX = CXOCF_2OCF_2CF_2Y$$
 (II)

wherein Y=F, OCF₃ or X as above defined, are preferred among the compounds of formula (I).

The perfluorovinyl ethers of formula:

$$CF_2 = CFOCF_2OCF_2CF_2Y$$
 (III)

wherein Y is as above defined, are particularly preferred. For example the perfluorovinyl ether of formula IV

$$CF_2 = CFOCF_2OCF_2CF_3$$
 (IV)

can be mentioned as particularly preferred perfluorovinyl ethers

Surprisingly, the vinyl ethers according to the invention show the advantages reported hereinafter with respect to the known vinyl ethers.

The advantages can be attributed to the $-\text{OCF}_2\text{O}--$ unit directly bound to the ethylene unsaturation.

6

The Tg lowering obtained with the vinyl ethers of the invention is connected to the presence of the ($-OCF_2O-$) unit directly bound to the unsaturation. The Tg lowering is so surprisingly evident that it can be defined as a primary effect

In fact, if the vinylether of the invention having two oxygen atoms is used:

$$CF_2 = CF - O - CF_2 - O - CF_2 CF_3$$
 (MOVE 1)

the Tg is clearly lower compared to the Tg of the polymer from PVE

$$CF_2 = CF - O - CF_2 CF_2 CF_3$$
 (PVE)

and to the polymer from the vinyl ether having the same formula, but with the second oxygen atom in a different position and not having the characteristic unit (—OCF₂O—), i.e.

$$CF_2 = CF - O - CF_2 CF_2 - O - CF_3$$
 (β-PDE)

It is surprising to notice that with respect to MVE

$$CF_2 = CF - O - CF_3$$

the β -PDE vinyl ether does not give any advantage as regards Tg of the resulting polymers.

On the contrary, the primary effect of the (—OCF₂O—) unit is very clear in the polymers of the vinyl ethers of the present invention (MOVE).

It has surprisingly been found that the (—OCF₂O—) unit bound to the ethylene unsaturation of the vinyl ethers of the invention drastically increases the vinylether reactivity, reducing the rearrangements to C(O)F which cause instability in the resulting polymer.

The advantages of the present invention can be summarized as follows.

The reactivity of the new monomers allows preparation of copolymers having a high MW (molecular weight) with a very low content of carboxylic groups or derivatives thereof such as —C(O)F or —COO—. The carboxylic group content in the copolymer of a monomer of the present invention with TFE is about 10 times lower than that of a copolymer prepared under the same conditions but using perfluoropropyl vinyl ether (PVE) instead of the inventive fluorovinyl ethers of the present invention (see the Examples). As noted, a lower content of carboxylic groups, or of the corresponding derivatives (amides, esters, etc.) results in more stable polymers.

The reactivity of the monomers of the present invention is surprisingly high (see the homopolymerization Examples). The fluorovinyl ethers of the invention can be used as comonomers both in plastomeric (per)fluoropolymers (containing crystalline domains) and in elastomeric (per)fluoropolymers. To obtain plastomeric polymers the amount of the vinylether of the invention must be such to allow and lead to the formation of crystalline domains, generally <10% by moles. The presence of crystalline domains can be determined by DSC. To obtain amorphous polymers the amount of the vinylether of the invention must be such to lead to the disappearance of the crystalline domains. The skilled man in the art can easily find the amount of the vinylether of the invention which is required for obtaining said results.

The novel fluorovinyl ethers of the present invention can be used in amounts as low as about 0.1% on a mole basis. Generally the amount of the vinyl ether for obtaining amorphous polymers is higher than 10% by moles (i.e. 10

mole %), preferably in the range from about 15 to 20% by moles, or higher. In the case of copolymers having a high content of vinyl ether monomer, the low temperature properties (e.g. T_g) of the polymers of the invention are clearly better compared to copolymers having the same MVE content (see the Examples) and also, surprisingly, compared to copolymers where the perfluorovinyl ether of equal number of oxygen atoms does not have a —OCF₂O group directly bound to the unsaturation, as in the case of the CF₂=CFOCF₂CF₂OCF₃ (β -PDE) (see the Examples).

The use of the monomers of the present invention in the polymerization reactions with fluoroolefins allows substantial and contemporaneous improvements over two important disadvantages of the prior art: the recovery of the unreacted vinylether and the polymer instability due to the presence of carboxylic end groups. A further advantage of the fluorovinyl ethers of the invention, as hereinafter illustrated, is that their preparation is carried out on a continuous basis by a limited number of steps. Furthermore, the raw materials used are inexpensive. The following raw materials can for 20 $CF_2(OF)_2$, example he mentioned $CF_2 = CF_2$ CF_2 = $CFOCF_3$, CHCl=CFCl, CFCl=CFCl, CF_2 =CFCl, CF₂=CFH, CF₂=CH₂, CHCl=CHCl and other olefins. The use of these reactants is specified in the synthesis process of the vinyl ethers of the invention.

When used in connection with a quantity the term about refers to such normal variation in that quantity as would be expected by the skilled artisan.

As used herein, essentially free of crystalline zones or regions means that crystallinity is not detected by, for example, DSC, under typical ordinary conditions as would be used by the skilled artisan in routine experiments.

Polymers, homopolymers and copolymers are obtainable by polymerizing the fluorovinyl ethers of general formula (I)–(IV) alone or with at least one other monomer.

By copolymer, a polymer containing units derived from the vinyl ether of the invention and one or more comonomers, is meant.

Preferred comonomers are fluorinated compounds having 40 at least one polymerizable double bond, C=C, optionally containing hydrogen and/or chlorine and/or bromine and/or iodine and/or oxygen.

Other comonomers that can be copolymerized with the fluorovinyl ethers of the present invention are non fluorinated C_2 – C_8 olefins, i.e. olefinically unsaturated hydrocarbons such as ethylene, propylene, and isobutylene.

Among the usable comonomers the following can be mentioned:

C₂–C₈ perfluoroolefins, such as tetrafluoroethylene (TFE), hexafluoropropene (HFP), hexafluoroisobutene;

 C_2 – C_8 hydrogenated fluoroolefins, such as vinyl fluoride (VF), vinylidene fluoride (VDF), trifluoroethylene, CH_2 –CH– R^2_f perfluoroalkylethylenes, wherein R^2_f is a C_1 – C_6 perfluoroalkyl group;

C₂-C₈ chloro- and/or bromo- and/or iodo-fluoroolefins, such as chlorotrifluoroethylene (CTFE) and bromotrifluoroethylene;

 CF_2 = $CFOR_f^2$ (per)fluoroalkyl vinyl ethers (PAVE), $_{60}$ wherein R_f^2 is a C_1 - C_6 (per)fluoroalkyl group, for example a trifluoromethyl, bromodifluoromethyl or a heptafluoropropyl group;

CF₂=CFOX^a (per)fluoro-oxyalkylvinyl ethers, wherein X^a is: a C_1 - C_{12} alkyl, or a C_1 - C_{12} oxyalkyl group, or a 65 C_1 - C_{12} (per)fluorooxyalkyl group having one or more ether groups, for example perfluoro-2-propoxypropyl.

8

sulphonic monomers having the structure CF_2 = $CFOX^bSO_2F$, wherein X^b = CF_2CF_2 , CF_2CF_2 , $CF_2CF(CF_2X^c)$ wherein X^c =F, CI, Br.

The process for preparing fluorinated polymers according to the present invention can be carried out by polymerization in organic solvent as described in U.S. Pat. Nos. 4,864,006 and 5,182,342, herein incorporated by reference. The organic solvent is selected from the group including chlorofluorocarbons, perfluoropolyethers, hydrofluorocarbons and hydrofluoroethers.

The process for preparing the polymers of the present invention can also be carried out by polymerization in aqueous emulsion according to well known methods in the art, in the presence of a radical initiator which can be selected from, for example: inorganic peroxides (for example alkaline metal or ammonium persulphates, perphosphates, perborates or percarbonates), optionally in combination with ferrous, cuprous or silver salts, or of other easily oxidizable metals; organic peroxides (for example, disuccinylperoxide, terbutylhydroperoxide, diterbutylperoxide); azocompounds (see U.S. Pat. Nos. 2,515,628 and 2,520,338, herein incorporated by reference). It is also possible to use organic or inorganic redox systems, such as ammonium persulphate/sodium sulphite or, hydrogen peroxide/aminoiminomethansulphinic acid to mentioned just a few.

Surfactants of various types are usually present in the reaction medium, among which the fluorinated surfactants of formula:

$$R^{3} - X^{-}M^{+}$$

wherein R³_f is a C₅–C₁₆ (per)fluoroalkyl chain or a (per) fluoropolyoxyalkyl chain, X⁻ is —COO⁻ or —SO₃⁻, M⁺ is selected from H⁺, NH₄⁺, and an alkali metal ion are particularly preferred. Among the most commonly used surfactants, ammonium perfluorooctanoate, (per) fluoropolyoxyalkylenes terminated with one or more carboxylic groups, etc. can be mentioned.

During the polymerization, known iodinated a brominated chain transfer agents can be added to the reaction medium. It is also possible to use as chain transfer agents alkaline or alkaline earth metal iodides or bromides, according to U.S. Pat. No. 5,173,553, herein incorporated by reference.

Other chain transfer agents are mentioned in U.S. Pat. No. 4,766,190, herein incorporated by reference.

Crosslinking of the amorphous polymers of the present invention can be carried out according to methods well known in the art. When, for example, one of the comonomers is vinylidene fluoride or vinyl fluoride, curing can be carried out with polyamines or aromatic polyols in the presence of suitable catalysts (accelerants) as described in U.S. Pat. Nos. 3,876,654 and 4,259,463. When the monomer is perfluorinated, one generally uses in the copolymerization, in amounts lower than or equal to 3%, a comonomer having a reactive site that includes, for example, Br, I, CN, OC₆F₅, COOR^a (wherein R^a is an alkyl from 1 to 5 carbon atoms), or double bonds as described in U.S. Pat. No. 5,268,405. When the polymer contains Br or I, it is cured in the presence of a peroxide or a polyunsaturated compound as described in U.S. Pat. Nos. 4,948,852, 4,948,853 and 4,983,60, and EP 683,149.

Another object of the present invention is the synthesis process of the new (per)fluorovinyl ethers, which comprises the reaction of hypofluorite $CF_2(OF)_2$ with fluorinated olefin of formula $R_1R_2C = CR_3R_4$ to give a first intermediate hypofluorite $F = CR_1R_2 = CR_3R_4 = OCF_2OF$, the subse-

quent reaction of said compound with a second fluorinated olefin of formula R₅R₆C=CR₇R₈ to give second intermediate F—CR₁R₂—CR₃R₄—OCF₂O—CR₅R₆—CR₇R₈—F, which is converted by an elimination reaction such as dehalogenation or dehydrohalogenation to the novel per- 5 fluorovinyl ethers.

The general scheme of the synthesis is as follows:

a)
$$CF_2(OF)_2+R_1R_2C=CR_3R_4\rightarrow F-CR_1R_2-CR_3R_4-OCF_2OF$$
 (VI)

b)
$$F-CR_1R_2-CR_3R_4-OCF_2OF+R_5R_6C^2=C^1R_7R_8$$

 $---\rightarrow F-CR_1R_2-CR_3R_4-OCF_2O-$
 $C^2R_5R_6-C^1R_7R_8-F$ (VII)

dehalogenation./

c)
$$F$$
— CR_1R_2 — CR_3R_4 — OCF_2O — $C^2R_5R_6$ — $C^1R_7R_8$ — F - - - \rightarrow ,

/dehydrohalogenation.

$$CFX = CXOCF_2OR \tag{I}$$

In this synthesis scheme, with reference to the formula of the compound (VII), R_1 , R_4 , are the same or different and are H, F; R₂, R₃; are the same or different and are H or Cl subject 25 to the following conditions; (1) when the final reaction is to be a dehalogenation, R₂=R₃ =Cl; (2) when the final reaction is to be a dehydrohalogenation one of the two substituents R_2 or R_3 is H and the other is Cl. Further R_5 , R_6 , R₇, R₈ are: F, or one of them is a C₁-C₄ linear or branched perfluoroalkyl group or a C1-C4 linear or branched perfluorooxyalkyl group containing from one to three oxygen atoms, or R5 and R7 or R6 and R8 are linked to each other to form with C^2 and C^1 a $C_5\text{--}C_6$ cyclic perfluoroalkyl group. Also, when one of the R_5 to R_8 radicals is a C_2 - C_4 linear or $_{35}$ branched fluoroalkyl or a C2-C4 linear or branched fluorooxyalkyl group containing from one to three oxygen atoms, one or two of the other R₅ to R₈ are F and one or two of the remainders, which can be the same as or different from each other, are selected from H, Cl, Br and; when two 40 substituents are selected from H, Cl, Br or I, they are both linked to the same carbon atom. When R_5 and R_7 or R_6 and R_8 are linked each other to form with $\check{C^2}$ and $\check{C^1}$ a $\check{C_5}$ – C_6 cycle fluoroalkyl group, one of the two free substituents R₆, R₈ or R₅, or R₇ is F and the other is selected from H, Cl, Br, 45 Iodine.

The fluoroalkene used in reaction a) is replaceable with that of the subsequent reaction b). In this case the meanings defined for the substituents of the R₁-R₄ group, and respectively of the R₅-R₈ group, are interchangeable each other, 50 with the proviso that the position of each radical of each of the two groups R₁-R₄ and R₅-R₈ with respect to —OCF₂O— on the chain of the intermediate compound (VII), is the same as would be if the synthesis takes place according to the above reported scheme and the two olefins 55 carried out at a heating rate of 10° C./min. each react in the considered steps.

In the first reaction a) of the above illustrated scheme, a hypofluorite gas flow CF₂(OF)₂, optionally suitably diluted with an inert fluid, comes into contact (i.e. is contacted with), in a suitable reactor with outlet, on the bottom of the 60 same (first reactor), with the R₁R₂C=CR₃R₄ olefin, optionally diluted in an inert fluid and preferably in gas flow, to allow the chemical reaction a) with formation of the intermediate hypofluorite (VI). To maintain the reaction stoichiometry, the reactants must be introduced into the reactor in 65 an approximately unitary molar ratio, or with an excess of CF₂(OF)₂. The residence time of the mixture in the reactor

10

can range from about a few hundredths of second (e.g. about 0.05 seconds) up to about 120 seconds depending on the olefin reactivity, the reaction temperature, and the presence of optional reaction solvents.

The reaction temperature can range from about -40° to about -150° C., preferably from about -80° to about -130°

The compound (VI) usually is not separated from the reaction product and it is transferred in a continuous way to 10 the subsequent reaction described in step b).

The mixture of the products coming out from the first reactor can be heated to room temperature before being fed into the second reactor.

In the second reaction b), the second olefin 15 $R_5R_6C = CR_7R_8$, pure or in solution, reacts with the product obtained in the first reaction with formation of compound

The olefin can be fed in a continuous way, so as to maintain its concentration constant in the reactor; except for that normal variation as would be expected by the skilled artisan. The temperature of the reaction b) can range from about -20° to about -130° C., preferably from about -50° to about -100° C. The olefin concentration is higher than or equal to about 0.01M, preferably the concentration is higher than 3M, more preferably the olefin in a highly purified state is used.

The solvents useful in steps a) and b) are perfluorinated or chlorohydrofluorinated solvents or hydrofluorocarbons. Examples of said solvents are: CF₂Cl₂, CFCl₃, CF₃CFH₂, CF₃CF₂CF₃, CF₃CCl₂H, CF₃CF₂Cl.

In reaction c), the compound (VII), after distillation from the reaction product, is subjected to dechlorination or to dehydrochlorination as the case may be to obtain the vinyl ethers of formula (I). This last step can be carried out by using reactions widely described in the-prior art. The suitable selection of the substituents R₁ to R₈ in the two olefins used in the synthesis allows one to obtain the vinyl ethers of the present invention.

Another object of the invention is a process wherein a hypofluorite of formula $X_1X_2C(OF)_2$ wherein X_1 and X_2 are the same or different and are F or CF₃, and two fluoroalkenes of formulas, respectively, $R_1^A R_2^A C = CR_3^A R_4^A$ and $R_5^A R_6^A C = CR_7^A R_8^A$, wherein $R_1^A - R_8^A$ are the same or different and are F, H, Cl, Br, I, $-CF_2OSO_2F$, $-SO_2F$, –C(O)F, C₁–C₅ linear or branched perfluoroalkyl or oxyperfluoroalkyl group, are reacted according to steps a) and b), excluding the dehalogenation or dehydrohalogenation step, to obtain compounds of general formula (VIII)

$$\begin{array}{lll} {\rm F-CR^{\it A}_{1}R^{\it A}_{2}-CR^{\it A}_{3}R^{\it A}_{4}-OCF_{2}O-CR^{\it A}_{5}R^{\it A}_{6}-} \\ {\rm CR^{\it A}_{7}R^{\it A}_{8}-E} & ({\rm VIII}) \end{array}$$

The following Examples are reported to illustrate the invention and they do not limit the scope of the same.

In the Examples the thermogravimetric analysis (TGA) is

EXAMPLE 1

Synthesis of CF₃CF₂OCF₂OCFClCF₂Cl perfluoro-1-2, dichloro-3,5-dioxaheptane

The reactor used is of the cylindrical type, with a total volume of about 300 ml and is equipped with magnetic dragging mechanical stirrer, turbine with recycle of the reacting gas placed at 20 cm from the reactor top, internal thermocouple, two internal copper pipes for the reactant feeding which end at about 1 mm from the turbine, and

45

50

11

product outlet from the bottom. In the reactor, the internal temperature of which is maintained at -114° C., 1.1 1/h (liters/hour) of $CF_2(OF)_2$ and 3.3 1/h of He are introduced through one of the two inlet pipes. A flow of 1.1 1/h of CF_2 = CF_2 and 0.7 1/h of He is maintained through the 5 second inlet pipe. Feeding is continued for 6.6 hours.

The residence time of the transport gas in the reaction zone, comprised of the space between the outlet of the two feeding pipes in the reactor and the inlet of the discharge pipe, is of about 4 sec.

From the reactor bottom the reaction products are brought to room temperature and the flow of gaseous mixture, monitored by gas chromatography, is fed in a continuous way, under mechanical stirring, into a second reactor having a 250 ml volume maintained at the temperature of -70° C. 15 and equipped with mechanical stirrer, thermocouple, dipping inlet for the reacting mixture, outlet with head of inert gas. The reactor contains 72.6 g of dichlorodifluoroethylene CFCl=CFCl.

At the end of the addition of reacting gases into the second ²⁰ reactor, the reaction raw material is distilled by a plate column at atmospheric pressure, collecting 41.5 g of the desired product (boiling point 91° C.).

The yield of perfluoro-1,2 dichloro-3,5-dioxaheptane, calculated with respect to $CF_2(OF)_2$, is 36%.

Characterization of perfluoro 1,2 dichloro-3.5-dioxaheptane

Boiling point at atmospheric pressure: 91° C.

¹⁹F-NMR spectrum in p.p.m. (with respect to CFCl₃ at 0): -51.3/-53.0 (2F, O—CF₂—O); -70.6/-72.6 (2F, C—CF₂Cl);

Mass spectrum (E.I. electronic impact), main peaks and respective intensities:

69 (48.6%); 119 (84.3%); 151 (76.86); 153 (69.8%); 185 (100%).

IR spectrum (cm⁻¹) intensity: (w)=weak, (m)=medium, (s)=strong, (vs)=very strong:

1407.3 (w); 1235.8 (vs); 1177.7 (vs); 1097.5(vs); 1032.2 (s); 929.3 (w); 847.9 (m).

EXAMPLE 2

Synthesis of CF₃OCF₂CF₂OCF₂OCFClCF₂Cl perfluoro-1,2-dichloro-3,5,8-trioxanonane (isomer A) and of CF₃OCF(CF₃)OCF₂OCFClCF₂Cl perfluoro-1,2-dichloro-3,5,7-trioxa-6-methyloctane (isomer B)

In a reactor identical to that used in Example 1, maintained at the same temperature of -114° C., 1.55 1/h of CF₂(OF)₂ and 4.5 1/h of He are introduced through one of 55 the two inlet pipes; through the second inlet pipe 1.4 1/h of CF₂=CF—OCF₃ and 0.7 1/h of He are fed for 4.5 hours.

The residence time of the transport gas in the reaction zone comprised between the reactor outlet and the end of the two feeding pipes is of about 3 sec.

On the reactor bottom the reaction products are brought to room temperature and the gaseous mixture flow, monitored by gas chromatography, is fed in a continuous way, under mechanical stirring, into a second reactor identical to the one used for the same step in Example 1. Inside, where a 65 temperature of -70° C. is maintained, there are 51 g of dichlorofluoroethylene CFCl—CFCl.

12

At the end of the addition of the reacting gases into the second reactor, the reaction raw material is distilled by a plate column at the reduced pressure of 250 mmHg. 50 g of a mixture formed by two isomers, respectively, isomer A) perfluoro-1,2-dichloro-3,5,8-trioxanonane and isomer 3) perfluoro-1,2-dichloro-3,5,7-trioxa-6-methyloctane are collected.

The mixture composition is determined by gas chromatography and is as follows: isomer A 79%, isomer B 21%. The molar yield of A+B with respect to the $CF_2(OF)_2$ used is 38%. The molar yield of A+B with respect to the used perfluoromethylvinylether is 42%. The isomers have been separated by preparative gas chromatography.

Characterization of Products A and B

Mixture boiling point (A 79%, B 21%) at the reduced pressure of 250 mmHg: 82° C.

¹⁹F-NMR spectrum in p.p.m. (with respect to CFCl₃ at 0) of the isomer A:

¹⁹F-NMR spectrum in p.p.m. (with respect to CFCl₃ at 0) of isomer B:

-50.0/-52.1 (2F, O—CF₂—O) -70.0/-71.8 (2F, C—CF₂CI);

-77.9 (1F, O—CFCl—C); -54.6/-54.9 (3F, CF₃OC): -85.7/-86.1 (3F, OC (CF₃)0); -100.3/-101.0 (1F, OCF (C)O).

Mass spectrum (electronic impact) main peaks and respective intensities:

Product A: 69 (50); 119 (100); 151 (50); 185 (42); 251 (38);

Product B: 69 (96); 97 (50); 135 (42); 151 (92); 185 (100). IR spectrum (cm⁻¹), intensity of the mixture A 79%, B 21%

((w)=weak, (m)=medium, (s)=strong, (vs)=very strong): 1388 (w); 1288 (vs); 1233 (vs); 1151 (vs); 1104 (vs); 1032 (s); 846 (m); 685 (w)

EXAMPLE 3

Synthesis of CF₃OCF₂CF₂OCF₂OCHClCHFCl perfluoro-1,2-dichloro-1,2-dihydro-3,5,8-trioxanonane (isomer C) and CF₃OCF(CF₃)OCF₂OCHClCHFCl perfluoro-1,2-dichloro-1,2-dihydro-3,5,7-trioxa-6methyloctane (isomer D)

In a reactor identical to that used in Example 1, maintained at the temperature of -112° C., 1.55 1/h of $CF_2(OF)_2$ and 4.5 1/h of He are introduced through one of the two inlet pipes. Through the second inlet pipe 1.4 1/h of CF_2 —CF— OCF_3 and 0.7 1/h of He are introduced for 5 hours.

The residence time of the transport gas in the reaction zone comprised between the reactor outlet and the end of the two feeding pipes is about 3 sec.

From the reactor bottom the reaction products are brought to room temperature and the gaseous mixture flow, monitored by gas chromatography, is fed in a continuous way, under mechanical stirring, into a second reactor identical to the one used for the same step in Example 1. Inside the second reactor the temperature is -70° C. and there are 50 g of 1,2-dichloroethylene CCIH—CCIH and 50 g of CFCl₃.

At the end of the addition of the reacting gases into the second reactor, after distillation of the solvent at room

pressure, the reaction raw material is distilled through a plate column at the reduced pressure of 100 mmHg. 43.5 g of the mixture of the desired products (isomer C 78%, isomer D 22%, determined by gas chromatography) are collected. The molar yield of C+D with respect to the used $CF_2(OF)_2$ is 533%. The isomers have been separated by preparative gas chromatography.

Characterization of Products C and D

Mixture boiling point (78%, D 22%) at the reduced $_{\rm 10}$ pressure of 100 mmHg: 71 $^{\circ}$ C.

¹⁹F-NMR spectrum in p.p.m. (with respect to CFCl₃ at 0) of the isomer C perfluoro-1,2-dichloro-1,2-dihydro-3,5,8-trioxanonane:

–56. 0/–57.2 (2F, O—CF
$$_2$$
—0); –143.2/–146.0 (1F, $_{15}$ C—CHFCl);

 $^{19}\mbox{F-NMR}$ spectrum in p.p.m. (with respect to CFCl₃ at 0) of the isomer D perfluoro-1,2-dichloro-1,2-dihydro-3,5,7- $_{20}$ trioxa-6-methyloctane:

$$-56.0/-57.2$$
 (2F, O—CF₂—O); $-143.2/-146.0$ (1F, C—CHFCI);

¹H spectrum-in p.p.m. (with respect to TMS) of the isomers C and D: 6.28/6.05 (1H —CHFCl); 6.02/5.95 (1H —CHCl—)

Mass spectrum (electronic impact), main peaks and ³⁰ respective intensities %: 69 (84); 119 (100); 185 (51.1); 251 (84); 281 (15.8); 283 (4.8); 347 (5.7); 349 (1.7)

IR spectrum (cm⁻¹) intensity ((w)=weak, (m)=medium, (s)=strong, (vs)=very strong): 3001.0 (w); 2920.9 (w); 2850.9 (w); 1286.3 (vs); 1233.7 (vs); 1125.5 (vs); 1081.8 ³⁵ (s); 1047.9 (s); 815.9 (m); 766.3 (m).

EXAMPLE 4

Dehalogenation of perfluoro 1,2-dichloro-3,5-dioxaheptane

In a 25 ml three-necked flask, equipped with mechanical stirrer, thermometer, dropping funnel, distillation column equipped with water refrigerant and collecting trap maintained at –78° C. and connected to a mechanical vacuum pump, 150 ml of DMF, 15 g of powdered Zn, 0.5 g of K₂CO₃, and 100 mg of I₂ are introduced. The internal temperature is brought to 80° C. and 50 g of perfluoro-1,2-dichloro-3,5-dioxaheptane are added dropwise. When the addition is over, the mixture is allowed to react for about 30 minutes. At the end, the internal pressure is gradually brought from 760 mmHg to 300 mmHg. After about 20 minutes, the collecting trap containing 34.2 g of perfluoro-3,5-dioxa-1-heptene (MOVE 1) is disconnected.

The dehalogenation yield is 85%.

Characterization of perfluoro-3,5-dioxa-1-heptene (MOVE 1)

Boiling point at atmospheric pressure: 41.9° C.

¹⁹F-NMR spectrum in p.p.m. with respect to CFCl₃ at 0:

-56.8 (2F, O—CF₂—O); -87.2 (3F, CF₃—C)

Mass spectrum (electronic impact), main peaks and 65 respective intensities: 69 (66.5%); 119 (100%); 147 (83.4%); 185 (89.4%); 216 (67.3%); 282 (8.2%).

14

IR spectrum (cm⁻¹) intensity ((w)=weak, (m)=medium, (s)=strong, (vs)=very strong: 1839.5 (m); 1407.6 (w); 1307.4 (vs); 1245.8 (vs); 1117.4 (vs); 907.2 (m); 846.0 (m).

EXAMPLE 5

Dehalogenation of the isomer Mixture A+B Obtained in Example 2 (perfluoro-1,2-dichloro-3,5, 8-trioxanonane CF₃OCF₂CF₂CF2OCFClCF₂Cl+ perfluoro-1,2-dichloro-3,5,7-trioxa-6-methyloctane CF₂OCF(CF₃)OCF₂OCFClCF₃Cl)

In a 250 ml flask equipped as described in the previous Example 4, 110 ml of DMF, 10 g of Zn in powder and 0.3 ml of Br₂ are introduced. The internal temperature is brought to 75° C. and 30.3 g of the binary mixture A+B separated in the previous Example 2 are added dropwise. When the addition is over, the mixture is allowed to react for about 3 hours. At the end, the internal pressure is gradually lowered from 760 mmHg to 200 mmHg at -79° C. After about 30 minutes the collecting trap is disconnected. The trap contents, which are washed with water, are recovered. Twentyfour grams of a mixture formed of 79% (gas chromatodetermination) perfluoro-3,5,8-trioxa-1-nonene graphic (MOVE '2) CF₃OCF₂CF₂OCF₂OCF=CF₂ (isomer A'), and 21% perfluoro-3,5,7-trioxa-6,methyl-1 octene (MOVE 2a) CF₂OCF(CF₃)OCF₂O—CF=CF₂ (isomer B') are obtained. The mixture is then separated by preparative gas chroma-

Characterization of Products A' and B'

Boiling range of the isomer mixture at atmospheric pressure: $72.5^{\circ}-74.5^{\circ}$ C.

 $^{19}\mbox{F-NMR}$ spectrum in p.p.m. (with respect to CFCl₃ at 0) of the isomer A': -55.9 (3F, CF₃—O); -56.9 (2F, O—CF₂—O); -90.8 (2F, C—CF₂—O); -91.2 (2F, O—CF₂—C); -114 (1F, O—C=C—F); -121.8 (1F, —O—C=CF); -137 (1F, O—CF=C)

¹⁹F-NMR spectrum in p.p.m. (with respect to CFCl₃ at 0) of the isomer B': -55.9 (3F, CF₃—0); -56.2 (2F, O—CF₂—O); -86.4 (3F, CF₃—C); -100.9 (1F, CF; -114 (1F, O—C=CF); -122 (1F, O—C=CF); -137 (1F, O—CF=C).

Mass spectrum (electronic impact), main peaks and respective intensities of the isomer A': 69 (74); 81 (18); 119 (100); 147 (59); 185 (26); 251 (21);

Mass spectrum (electronic impact), main peaks and respective intensities of the isomer B': 69 (80); 81 (37); 97 (47); 119 (36); 147 (100); 185 (19).

IR spectrum (cm⁻¹) intensity ((w)=weak, (m)=medium, (s)=strong, (vs)=very strong): 1839 (m); 1343 (s); 1248 (vs); 1145 (vs); 918 (m); 889 (m).

EXAMPLE 6

Dehalogenation of the isomers C+D Mixture
Obtained in Example 3
(CF₃OCF₂CF₂OCF₂OCHClCHFCl perfluoro-1,2-dichloro-1,2-dihydro-3,5,8-trioxanonane (isomer C)+CF₃OCF(CF₃) OCF₂OCHClCHFCl perfluoro-1,2-dichloro-1,2-dihydro-3,5,7-trioxa-6-methyloctane
(isomer D))

In a 500 ml three-necked flask, equipped with mechanical stirrer, thermometer, dropping funnel, distillation column having a water refrigerant and a collecting trap maintained

15

at the temperature of -78° C., 250 ml of DMF, 30 g of zinc powder, and 300 mg of I₂ are introduced.

The temperature is brought to 100° C. and 56.9 g of the isomer mixture obtained in Example 3 are added dropwise.

When the addition is, over the reactor internal temperature 5 is brought to 120° C. and stirring is maintained for 24 hours. At the end, the reaction product, which contains traces of solvent and which is collected in the trap maintained at -78° C., is distilled. After washing with water, 35 g of a mixture of perfluoro-1,2-dihydro-3-5-8-trioxa-1-nonene (isomer C', 79% by mole) and of perfluoro-1,2-dihydro-3-5-7-trioxa-5methyl-1-octene (isomer-D', 21% by mole) is recovered. The isomers are separated by preparative gas chromatography.

The dehaloagenation reaction yield is 76%.

Characterization of Products C' and D'

Boiling range of the mixture of-isomers C' 79%, D' 21% at atmospheric pressure: 90.0°–92.0° C.

¹⁹F-NMR spectrum in p.p.m. (with respect to CFCl₃ at 0) of the isomer C' perfluoro-1,2-dihydro-3,5,8-trioxa-1-non-

¹⁹F-NMR spectrum in p.p.m. (with respect to CFCl₃ at 0) of the isomer D' perfluoro-1,2-dihydro-3,5,7-trioxa-6-methyl-1-octene: -55.0 (3F, CF₃—0); -56.9 (2F, O—CF₂—0); -86.2 (3F, CF₃—C); -101.0 (1F, CF) -149.3/-150, 0 (1F,

Mass spectrum (electronic impact), main peaks and respective intensities %: 69 (82); 119 (100); 185 (29); 246 (25); 251 (20); 312 (43).

IR spectrum (cm⁻¹) intensity of the isomer mixture (C' =very strong): 3140 (w); 1722 (w); 1695 (w); 1402 (m); 1281 (vs); 1237 (vs); 1147 (vs); 1106 (vs); 1030 (m).

EXAMPLE 7

Homopolymerization of perfluoro-3 5-dioxa-1-heptene (MOVE 1)

In a glass reactor for polymerization, having a 20 ml volume, equipped with magnetic stirrer and with an inlet for 45 the reactant feeding and discharge, 60 µl of perfluoropropionylperoxide at 3%. by weight in CFCl₂CF₂Cl and 3 g of MOVE 1 are sequentially introduced. The so-charged reactor is-brought to the temperature of -196° C., evacuated, brought to room temperature. The cooling-evacuation pro- 50 cedure is repeated. At the end of the degassing operations the reactor is thermostated at the temperature of 30° C. and the mixture is allowed to react under these conditions for two days with magnetic stirring.

The reaction raw material which is finally recovered 55 of the autoclave is analyzed by gas chromatography. appears as a slightly viscous, transparent, colourless and homogeneous solution.

After distillation of the unreacted monomer and subsequent stripping under vacuum at 150° C. for 3 hours, 180 mg of the polymer are separated.

The IR analysis of the obtained polymer shows that, in the spectrum, absorption bands in the region of fluorinated double bonds are absent.

The 19F-NMR analysis carried out on the polymer dissolved in C₆F₆ is in accordance with the homopolymer 65 structure having a molecular weight of 50,000. The analysis does not show the presence of unreacted monomer.

16

The DSC thermogram does not show any melting endothermic curve, wherefore the polymer is amorphous. The polymer T_a, determined by DSC, is -35.4° C. The thermogravimetric analysis (TGA) shows a weight loss of 2% at 332° C. and of 10% at 383° C.

EXAMPLE 8

Copolymer Between perfluoro-3,5,8-trioxa-1-nonene CF₃OCF₂CF₂OCF₂OCF=CF₂ (MOVE 2) and perfluoro-3,5,7-trioxa-6, methyl-1-octene CF,OCF $(CF_3)OCF_2O-CF-CF_2$ (MOVE 2a)

In a reactor having the same characteristics as that 15 described in Example 7, 150 μl of perfluoropropionylperoxide at 3% by weight in CFCl₂CF₂Cl and 3.2 g of a mixture prepared according to the process of Example 5 and containing 83% MOVE 2 and 17% MOVE 2a, are introduced. The reactor is then evacuated, cooled, and the subsequent reaction carried out as described in the previous Example 7.

The raw reaction product appears as a slightly viscous, transparent, colourless and homogeneous solution. The unreacted monomers are distilled and a stripping under vacuum at 150° C. for 3 hours is thereafter carried out. Finally, 350 mg of the polymer are separated.

The IR analysis shows that, in the polymer spectrum, absorption bands in the region of the fluorinated double bonds are absent.

The ¹⁹F-NMR analysis is in accordance with the copolymer structure having an average molecular weight of 35,000 and a MOVE 2/MOVE 2a content equal to the percentages of the respective monomers in the reacting mixture. Unreacted monomers are not evident.

The DSC thermogram does not show any melting endot-79%, D' 21%) ((w)=weak, (m)=medium, (s)=strong, (vs) 35 hermic curve, wherefore the polymer is amorphous. The polymer T₂, determined by DSC, is -52.6° C. The thermogravimetric analysis (TGA) shows a weight loss of 2% at 280° C. and of 10% at 327° C.

EXAMPLE 9

Crystalline copolymer Between MOVE 1 and TFE

A 5 1 steel AISI 316 autoclave with stirrer operating at 650 rpm is used. After evacuation of the autoclave, 3 1 of demineralized water, 15.70 g of MOVE 1 and the microemulsion prepared according to the procedure described in U.S. Pat. No. 4,864,006 are sequentially introduced, so as to have a concentration of 2 g of surfactant/l of water.

The autoclave is heated to 75° C. and then pressurized to 0.32 bar with ethane. A gaseous mixture in a molar ratio of 54.55 TFE/MOVE 1 is pumped by a compressor until internal pressure on the autoclave is 21 absolute bar.

The composition of the gaseous mixture present in the top

Before the reaction is started, the gaseous phase has the following molar percentages of the reactants: 93.1% TFE, 5.5% MOVE 1 and 1.4% Ethane. The reaction is triggered by feeding, in a continuous way by a metering pump a 0.0031 molar potassium persulphate solution at a flow rate of 88 ml/h.

The pressure is maintained constant by feeding additional monomer mixture. The polymer synthesis is stopped after 742 g of mixture have been fed in total.

The reactor is cooled to room temperature, the emulsion is discharged, and coagulation is induced by addition of HNO, (65%).

The polymer is separated, washed with water and, dried at

The IR analysis shows the presence of very small absorption bands in the carboxyl zone, the intensity of which is about half of that obtained for a TFE/PVE copolymer film 5 having the same thickness, prepared according to the comparative Example 3. The MFI according to ASTMVD 1238-52T was 4.4. The polymer therefore is thermally more stable (see the comparative Example hereunder).

EXAMPLE 10

Amorphous copolymer Between MOVE 1 and TFE

In an AISI-316 polymerization reactor having a 40 ml 15 volume, equipped with magnetic stirring, pressure transducer, and an inlet for the reactant feeding and discharge, 250 µl of perfluoropropionylperoxide at 3% by weight in CFCl₂CF₂Cl, 9.8 mmoles of MOVE 1, and 18 mmoles of tetrafluoroethylene are introduced.

The reactor is cooled to -196° C., evacuated, then brought to room temperature. The cooling-evacuation procedure is repeated twice.

At the end of the degassing operations, the reactor is thermostated at the temperature of 30° C. and the reaction 25 mixture maintained under magnetic stirring. The internal pressure decreases from 6.4 atm to 4.7 atm in about 8 hours (reaction time).

After distillation of the unreacted monomers and polymer stripping under vacuum for 3 hours at 150° C., 1,100 mg of 30 polymer are recovered. The polymer appears as a transparent and colourless rubber.

By 19F-NMR analysis of the polymer dissolved with heating in C₆F₆, it is determined that the MOVE 1 molar percentage in the polymer is 24%.

The IR analysis does not show, in the polymer spectrum, absorption bands in the region of the fluorinated double bonds and shows the presence of very small absorption bands in the region of the carboxyl bands. The intensity of these signals, compared to ones in the same region obtained 40 10% at 455° C. from a film having the same thickness but made of polymer of the comparative Example 1, is equal to about 1/10 of the

The DSC thermogram does not show any melting endotherm, wherefore the polymer is amorphous. The T_g deter- 45 mined by DSC is -21.4° C.

The TGA shows a weight loss of 2% at 450° C. and of 10% at 477° C. The polymer therefore is thermally more stable (see the comparative Example hereunder) with respect to the comparative Example (see below).

The polymer intrinsic viscosity measured at 30° C. in Fluorinert® FC-75, is 35.5 ml/g.

EXAMPLE 11

Amorphous copolymer Between MOVE 1 and TFE

In an AISI-316 polymerization reactor identical to that described in the previous Example 10, 250 µl of perfluoropropionylperoxide at 3% by weight in CFCl₂CF₂Cl, 9.75 60 mmoles of MOVE 1 and 9 mmoles of tetrafluoroethylene are sequentially introduced.

The procedure already described in the previous Example 10 is followed until the thermostating step at the temperature of 30° C. under magnetic stirring. During the reaction the 65 internal pressure decreases from 3.4 atm to 2.9 atm in about 8 hours.

18

At the end, the unreacted monomers are distilled and the polymer is stripped under vacuum at 150° C. for 3 hours. 480 mg of the polymer are separated.

By ¹⁹F-NMR analysis of the polymer dissolved with

heating in C₆F₆, it is determined that the MOVE 1 molar percentage in the polymer is 39%.

The IR analysis shows that, in the polymer spectrum, absorption bands in the region of the fluorinated double bonds are absent.

The DSC thermogram does not show any melting endothermic curve, wherefore the polymer is amorphous. The T_o determined by DSC is -29.8° C.

The TGA shows a weight loss of 10% at 435° C.

EXAMPLE 12

Amorphous copolymer Between MOVE 1 and $CF_2 = CH_2$

In a polymerization reactor identical to that described in Example 10, 250 µl of perfluoropropionylperoxide at 3% by weight in CFCl₂CF₂Cl, 10 mmoles of MOVE 1, and 18 mmoles of VDF are sequentially introduced.

The procedure already described in the previous Example 10 is followed until the thermostating step at the temperature of 30° C. under magnetic stirring. The internal pressure decreases from 6.8 atm to 5.0 atm during the reaction (about 8 hours).

After distillation of the unreacted monomers and subsequent polymer stripping under vacuum at 150° C. for 3 hours, 1,600 mg of the polymer are separated, appearing as a transparent and colourless rubber.

By the ¹⁹F-NMR analysis carried out on the polymer dissolved in C₆F₆ it is determined that the MOVE 1 molar 35 percentage in the polymer is 40%.

The DSC thermogram does not show any melting endothermic curve, wherefore the polymer is amorphous. The T_g determined by DSC, is -47° C.

The TGA shows a weight loss of 2% at 428° C. and of

EXAMPLE 13

Amorphous terpolymer MOVE 2/MOVE 2a/TFE

In a polymerization reactor identical to that described in Example 10, 100 µl of perfluoropropionylperoxide at 6% by weight in CFCl₂CF₂Cl, 10 mmoles of a MOVE 2 (83%) and MOVE 2a (17%) mixture (synthesized according to the process of Example 5), and 18 mmoles of tetrafluoroethylene (TFE) are sequentially introduced.

The procedure already described in the previous Example 10 is then followed until thermostating at the temperature of 30° C. under magnetic stirring. The internal pressure ₅₅ decreases from 6.1 atm to 3.9 atm during the reaction (about 8 hours).

After distillation of the unreacted monomers and polymer stripping under vacuum at 150° C. for 3 hours, 1,131 mg of the polymer are separated.

By the ¹⁹F-NMR analysis carried out on the polymer dissolved in C₆F₆, the total molar percentage of the MOVE 2+MOVE 2a perfluorovinyl ethers units in the polymer is 22%; the MOVE 2/MOVE 2a ratio by moles in the polymer is 83/17 (equal to that of the starting feed mixture).

The presence of unreacted monomers is not evident.

The IR analysis does not show, in the polymer spectrum, absorption bands in the region-of the fluorinated double

bonds, and it shows the presence of very small absorption bands in the zone of the carboxyl signals. The intensity of these signals, compared with the similar ones obtained from a film having the same thickness obtained with the polymer of the comparative Example 1, is equal to about $\frac{1}{10}$ of the $\frac{5}{10}$ latter

The DSC thermogram does not show any melting endotherm, wherefore the polymer is amorphous. The $\rm T_g$ determined by DSC, is –37.5° C.

The TGA shows a weight loss of 10% at 473° C. The polymer intrinsic viscosity measured at 30° C. in

The polymer intrinsic viscosity measured at 30° C. i. Fluorinert® FC-75, is 40.0 ml/g.

EXAMPLE 14

Amorphous terpolymer MOVE 2/MOVE 2a/TFE

In a polymerization reactor identical to that described in Example 10, 100 μ l of perfluoropropionylperoxide at 6% by weight in CFCl₂CF₂Cl, 9.7 mmoles of the MOVE 2 (83%) 20 and MOVE 2a (17%) mixture synthesized according to the process of Example 5, and 10 mmoles of tetrafluoroethylene (TFE) are sequentially introduced.

The procedure already described in the previous Example 10 is then followed until the thermostating step at the 25 temperature of 30° C. under magnetic stirring. The internal pressure decreases from 3.6 atm to 2.7 atm during the course of reaction (about 8 hours).

After distillation of the unreacted monomers and polymer stripping under vacuum at 150° C. for 3 hours, 652 mg of $_{30}$ polymer are separated.

By the ¹⁹F-NMR analysis carried out on the polymer dissolved in C₆F₆ the total molar percentage of units derived from the MOVE 2+MOVE 2a perfluorovinyl ethers in the polymer is 37%; the MOVE 2/MOVE 2a molar ratio in the 35 polymer is 83/17 (equal to that of the starting feed mixture).

The presence of unreacted monomers is not evident.

The IR analysis does not show, in the polymer spectrum, absorption bands in the region of the fluorinated double bonds

The DSC thermogram does not show any melting endothermic curve, wherefore the polymer is amorphous. The T_g determined by DSC, is -44.5° C.

The TGA shows a weight loss of 10% at 451° C.

The polymer intrinsic viscosity measured at 30° C. in 45 Fluorinert® FC-75, is 16.7 ml/g.

EXAMPLE 15

Amorphous copolymer Between perfluoro-1,2-dihydro-3,5,8-trioxa-1-nonene (H-MOVE 2) and perfluoro-1,2-dihydro-3,5.7-trioxa-6-methyl-1-octene (H-MOVE 2a) with molar ratio 88/12

In a reactor identical to that described in Example 7, 200 $_{55}$ μl of perfluoropropionylperoxide at 3% by weight in CFCl₂—CF₂Cl and 3.1 g of an 88/12 H-MOVE 2/H-MOVE 2a 88/12 mixture are introduced.

The procedure described in Example 7 is followed.

The recovered reaction raw material appears as a slightly 60 viscous, transparent, colourless and homogeneous solution.

After distillation of the unreacted monomer and subsequent stripping under vacuum at 150° C. for 3 hours, 120 mg of polymer are separated.

The IR analysis of the polymer obtained shows that, in the 65 polymer spectrum, absorption bands in the region of the fluorinated double bonds are absent.

20

The ¹⁹F-NMR analysis is in accordance with the copolymer structure having a content of monomers H-MOVE 2 and H-MOVE 2a equal to the H-MOVE 2 and H-MOVE 2a percentages in the reacting mixture. The analysis does not show the presence of unreacted monomers.

The DSC thermogram does not show any melting endotherm, wherefore the polymer is amorphous. The polymer T_g determined by DSC, is -58.0°C. The thermogravimetric analysis (TGA) shows a weight loss of 10% at 307° C.

EXAMPLE 16

Terpolymer H-MOVE 2/H-MOVE 2a/TFE

In a reactor similar to that described in Example 10, 100 μl of perfluoropropionylperoxide at 6% by weight in CFCl₂—CF₂Cl, 5 mmoles of a H-MOVE 2 (88%) and H-MOVE 2a (12%) mixture, and 18 mmoles of tetrafluoroethylene are introduced.

The same procedure described in Example 10 is followed. At the end of the degassing, the reactor is thermostated at the temperature of 30° C. under magnetic stirring. The internal pressure decreases from 6.8 atm to 6.5 atm in about 6 hours (reaction time).

After distillation of the unreacted monomers and polymer stripping under vacuum at 150° C. for 3 hours, 300 mg of the polymer are separated.

By 19 F-NMR analysis of the polymer dissolved under heating in C_6F_6 it is calculated that the molar percentage (mole %) of units derived from the perfluorovinyl ethers (H-MOVE 2+H-MOVE 2a) contained in the polymer is 33%. The H-MOVE 2/H-MOVE 2a molar ratio in the polymer is equal to the H-MOVE 2/H-MOVE 2a molar ratio of the feed mixture. Unreacted monomers are not evident.

The IR analysis does not show, in the polymer spectrum, absorption bands in the zone of the fluorinated double bonds.

The DSC thermogram does not show any melting endotherm, wherefore the polymer is amorphous. The T_g determined by DSC, is -44.5° C.

The TGA shows a weight loss of 10% at 450° C.

EXAMPLE 1 (COMPARATIVE)

Copolymer PVE/TFE

In a polymerization reactor identical to that described in Example 10, 250 μ l of perfluoropropionylperoxide at 3% by weight in CFCl₂CF₂Cl, 9.8 mmoles of PVE, and 18 mmoles of tetrafluoroethylene, are sequentially introduced.

The procedure already described in the previous Example 10 is followed until thermostating at the temperature of 30° C. under magnetic stirring. The reaction time is eight hours.

After distillation of the unreacted monomers and stripping under vacuum at 150° C. for 3 hours, 540 mg of the polymer are recovered.

By the $^{19}\text{F-NMR}$ analysis carried out on the polymer dissolved in C_6F_6 , it is calculated that the PVE molar percentage in the polymer is 23%.

The IR analysis shows that, in the polymer spectrum, there are absorption bands in the carboxyl zone, whose intensity is 10 times higher than that obtained from a film of a MOVE 1/TFE copolymer prepared according to Example 10 and having the same thickness.

The DSC thermogram does not show any melting endothermic curve, wherefore the polymer is amorphous. The TGA shows a weight loss of 2% at 427° C. and of 10% at 463° C. The Tg, determined by DSC, is $+15^{\circ}$ C.

The polymer intrinsic viscosity, measured at 300 C in Fluorinert® FC-75, is 51 ml/g.

EXAMPLE 2 (COMPARATIVE)

Copolymer Between β-PDE (CF₃OCF₂CF₂ OCF=CF₂)/TFE

In a polymerization reactor identical to that described in Example 10, 250 μ l of perfluoropropionylperoxide at 3% by $_{10}$ weight in CFCl $_2$ —CF $_2$ Cl, 10 mmoles of β -PDE, and 18 mmoles of tetrafluoroethylene, are in sequence introduced.

The procedure described in the previous Example 10 is followed until the thermostating step at the temperature of 30° C. under magnetic stirring.

By the ¹⁹F-NMR analysis carried out on the polymer purified of monomers by the processes described in the previous Examples, it is calculated that the molar percentage of β-PDE in the polymer is 23%.

The DSC thermogram does not show any melting endothermic curve wherefore the polymer is amorphous. The T_g , determined by DSC, is -4.8° C.

This Tg value is clearly higher than those obtainable with the vinyl ethers of the invention (see the above Examples).

EXAMPLE 3 (COMPARATIVE)

Crystalline Copolymer PVE/TFE (PFA)

One operates as in Example 9 except that in this case the $_{30}$ perfluoropropylvinyl ether (PVE) is used instead of α -PDE to obtain a copolymer having MFI equal to that of the Example copolymer of 9.

The IR analysis shows absorption bands in the carboxyl zone, the intensity is of which double those obtained for a 35 TFE/MOVE 1 copolymer film of equal thickness and prepared according to Example 9.

I claim:

1. A polymer obtained by the polymerization, alone or in combination with one or more copolymerizable comonomers, of a fluorovinyl ether of formula:

CFX=CXOCF2OCF2CF2OCF3

wherein X is F or H.

- 2. The polymer of claim 1 wherein the fluorovinyl ether is copolymerized with one more comonomers that is a fluorinated compound having at least one polymerizable carbon-carbon double bond.
- 3. The polymer of claim 2 wherein the fluorinated compound further comprises at least one atom selected from the group consisting of hydrogen, chlorine, bromine, iodine, and oxygen.
- **4**. The polymer of claim **1** wherein the fluorovinyl ether is copolymerized with one or more comonomers that is a C_3-C_8 olefinically unsaturated hydrocarbon.
- ²5. The polymer of claim 1 wherein the fluorovinyl ether is copolymerized with one or more comonomers selected from the group consisting of:
 - (a) a C_2 - C_8 perfluoroolefin;
 - (b) a C₂-C₈ fluoroolefin;
 - (c) a C_2 – C_8 chlorofluoroolefin, a C_2 – C_8 bromochloroolefin, and a C_2 – C_8 iodofluoroolefin;
 - (d) a fluoroalkyl vinyl ether, having the structure CF₂=CFOR²_f, wherein R²_f is a C₁-C₆ perfluoroalkyl group in which 0 or 1 of the fluorine atoms are replaced with an atom selected from bromine or chlorine;

- (e) a perfluorooxyalkylvinyl ether of structure CF²=CFOX^a wherein X^a is selected from a C₁-C₁₂ alkyl group, a C₁-C₁₂ oxyalkyl group, and a C₁-C₁₂ fluorooxyalkyl group having at least one ether oxygen; and
- (f) a sulphonic monomer having the structure CF_2 = $CFOX^bSO_2F$, wherein X^b can be CF_2CF_2 , $CF_2CF_2CF_2$, or $CF_2CF(CF_2X^c)$, and wherein X^c is selected from F, Cl, Br.
- **6**. The polymer of claim **5** wherein the fluorovinyl ether is copolymerized with a perfluoroolefin selected from the group consisting of a tetrafluoroethylene (TFE), a hexafluoropropene (HFP), and a hexafluoroisobutene.
- 7. The polymer of claim 5 wherein the fluorovinyl ether is copolymerized with a fluoroolefin selected from the group consisting of a vinyl fluoride (VF), a vinylidene fluoride (VDF), a trifluoroethylene, a chlorotrifluoroethylene (CTFE), a bromotrifluoroethylene, and a fluoroolefin of structure CH₂=CH—R²_f, wherein R²_f is a C₁-C₆ perfluoroalkyl group.
 - **8**. The polymer of claim **5** wherein the fluorovinyl ether is copolymerized with a fluoroalkyl vinyl ether having the structure CF_2 — $CFOR_f^2$ wherein R_f^2 is selected from the group consisting of a trifluoromethyl group, a bromodifluoromethyl group, and a heptafluoropropyl group.
 - **9**. The polymer of claim **5** wherein the fluorovinyl ether is copolymerized with a fluoroalkyl vinyl ether, having the structure CF_2 = $CFOR^2_f$ wherein R^2_f is a C_1 - C_6 perfluoroalkyl group that is a perfluoro-2-propoxypropyl group.
 - 10. The polymer of claim 1 wherein the amount of the fluorovinyl ether polymerized is between about 0.1 mole % and about 20 mole %, the remainder comprising the one or more copolymerizable comonomers.
 - 11. The polymer of claim 10 wherein the amount of the fluorovinyl ether polymerized is between about 15 mole % and about 20 mole %, the remainder comprising the one or more copolymerizable comonomers.
 - 12. The polymer of claim 1 wherein the polymer is elastomeric.
 - 13. The polymer of claim 1 wherein the polymer is plastomeric.
 - **14**. A fluoroelastomer according to claim **1**, comprising units derived from fluorovinyl ethers of formula CF₂—CFOCF₂OCF₂CF₂OCF₃.
 - 15. The fluoroelastomer of claim 14 further comprising in the polymer chain, units derived from either:
 - 1) a vinylidene fluoride and at least one additional copolymerizable comonomer selected from a C₂-C₈ perfluoroolefin; a C₂-C₈ chlorofluoroolefin; a C₂-C₈ bromofluoroolefin; a C₂-C₈ iodofluoroolefin; a fluoroalkyl vinyl ether of structure CF₂=CFOR'_f, wherein R'_f is a C₁-C₆ alkyl group in which from one up to all hydrogen atoms are replaced with fluorine atoms; a perfluorooxyalkyl vinyl ether of structure CF₂=CFOX', wherein X' is a C₁-C₁₂ perfluorooxyalkyl group having one or more ether oxygens; and a C₂-C₈ olefin; or
 - 2) a tetrafluoroethylene and at least one additional copolymerizable comonomer selected from a fluoroalkyl vinyl ether of structure CF₂—CFOR'_f, wherein R'_f is as above defined; a perfluorooxyalkyl vinyl ether of structure CF₂—CFOX', wherein x' is as above defined; a C₂-C₈ fluoroolefin; a chlorofluoroolefin; a bromofluoroolefin; a iodofluoroolefin; and a C₂-C₈ olefin.

* * * * :